



- Highly visible with integrated illumination for those with 'low vision'.
- Highly tactile for ease of use by those with 'no vision'.
- Responsive keys move with a positive tactile dynamic.

illumination

- 3.5mm audio jack socket, illuminated for ease of location.
- Integrated sound volume control.
- Designed for fixed, under-panel, installation in host equipment.
- Connection to host via a single USB cable (supplied separately).
- Version available with integrated support for Storm's Touchless-CX functionality.
- Compliant with current accessibility mandates.
- Also available with integrated support for headset microphone (please see part numbers below).

USB 2.0 cable, 0.9m long, angled mini-B male connector to Type A male connector

AudioNav – 1400 Series	Part Numbers
AudioNav, 6 keys, with audio & headset mic support, green LED AudioNav, 6 keys, with audio & headset mic support, white LED	1406-34001 1406-34011
AudioNav, 6 keys, with audio & headset mic support, Touchless-CX, green LED AudioNav, 6 keys, with audio & headset mic support, Touchless-CX, white LED	1406-35001 1406-35011

## **AudioNav Keypad**

## AudioNav is an assistive USB device offering menu navigation by means of audio direction.

Users with impaired vision, reading difficulties or impaired fine motor skills can navigate through menus or directories that would typically be presented on a visual display or touch screen. Screen content is presented and summarised by recorded or synthesized language via a headset or handset. Menu pages and available options can be reviewed and selected using this responsive and highly tactile keypad device.

The AudioNav device is intended for use as the tactile/audio interface for any ADA or EAA compliant application such as kiosks, ticketing machines, vending machines, voting terminals etc.

> AudioNav is available in two physical configurations (original and alternative). The alternative (ALT) version utilises a different micro-processor, has some minor dimensional differences and requires slightly longer screw fixings. Both options are available with Touchless-CX technology.



The Storm Touchless-CX app enables kiosk users to intuitively navigate content displayed on a kiosk touchscreen. This is achieved using their personal smartphone or tablet device, without having to physically touch the kiosk screen.



107.10

All dimensions in mm







& Touchless-CX are trademarks of Keymat Technology Ltd. These products include proprietary technology and intellectual property retained by Keymat Technology Ltd (trading as Storm Interface). All riobte:

4500-01

## Performance

83.30

Vibration & Shock: Impact Resistance: Certification: EMC: ESD Immunity: ADA / EEA:

**Environmental** Weather Resistance:

Operational temperature: **Specification** 

Rating: Connection: Audio:

**Underpanel Depth:** 

ETSI 6M3 IK08 (5J Rating) CE / FCC / UL EN55022 Class B 15kV Contact and Air

Compliant

-20°C to +70°C (drv)

IP65 (when panel mounted)

5V + 0.25V (USB 2.0) Mini USB B Socket 3.5mm Audio Jack Socket

(Illuminated) 25mm

For more information & to order: www.storm-interface.com

ATP1400AN JUNE 2024









