

DEGL1200



203

- Rated for continuous use in exposed outdoor environments
- Dual Voltage 500mA / 12VDC 250mA / 24VDC
- Supplied complete with armature and fixing hardware
- Integral voltage spike suppressor
- 2 Year limited warranty
- Designed to meet UL/cUL/CE/FCC requirements

Description 12V/24V DC **Electro-Magnetic** Door Lock **DEG1200** Model **Holding Force** 1200 Pounds Installation Secured perimeter **Environment High security Exposed external** locations

63 All dimensions in mm

Specified for use with Storm AXS Access Control Solutions

42

Storm-AXS StrikeMaster keypads

Storm-AXS Power supply

Storm-AXS Touch-free exit switch

Storm-AXS Emergency override switch (break glass)

Part Numbers

DR2KW20, DR2KT20, DE1KT10

DEPS030 DEEX010 DEEM010


12V/24V Electro-Magnetic **Door/Gate Lock**

For use in exposed, outdoor locations, this robust and weather resistant mag-lock is ideal for installation at external doors or perimeter gates.

Unlike conventional locks Storm AXS surface mounted mag-locks require minimal modification of doors or frames and are ideal for all types of doors, including iron doors and gates, glass doors or doors surrounded by glass panels. Installation is quick and easy using basic tools (no carpentry skills required). Doors and frames are not weakened or compromised during installation. The installed lock is discreet but very secure. With up to 1200 pounds holding force; most doors or gates will break before the lock lets go. The lock is supplied complete with fixing brackets, armature plates and comprehensive installation instructions for both inward and outward opening doors or gates.



There are Storm AXS Mag-locks available for both external and internal doors.





For more information & to order:

You



www.storm-interface.com



FM 39602





