







- Supplied complete with armature and fixing hardware
- Dual Voltage 500mA / 12VDC 250mA / 24VDC
- Integral voltage spike suppressor
- 2 Year limited warranty
- Designed to meet UL/cUL/CE/FCC requirements

Description 12V/24V DC **Electro-Magnetic Door Lock DEL1200** Model **Holding Force** 1200 Pounds Installation Secured perimeter **Environment** High security Internal / sheltered external locations

## 12V/24V Electro-Magnetic **External/Perimeter Door Lock**

Powerful electro-magnetic door locks are the most convenient and effective way to achieve secure access control.


Unlike conventional locks Storm AXS surface mounted mag-locks require minimal modification of doors or frames and are ideal for all types of doors, including iron doors and gates, glass doors or doors surrounded by glass panels. Installation is quick and easy using basic tools (no carpentry skills required). Doors and frames are not weakened or

compromised during installation. The installed lock is discreet but very secure, with up to 1200 pounds holding force. Most door frames will break before the lock lets go. The lock is supplied complete with fixing brackets, armature plates and comprehensive installation instructions for both inward and

outward opening doors. There are Storm AXS Mag-locks available for

both external and internal doors.







For more information & to order:

## Specified for use with Storm AXS Access Control Solutions

Storm-AXS StrikeMaster keypads

Storm-AXS Power supply

Storm-AXS Touch-free exit switch

Storm-AXS Emergency override switch (break glass)

## Part Numbers

DR2KW20, DR2KT20, DE1KT10

DEPS030 DEEX010 DEEM010







www.storm-interface.com





FM 39602

