



M3 x 20mm LONG STEEL WELD STUDS
OR EQUIVALENT (6-32UNC).

DIRECTIONAL KEYPAD IS DESIGNED TO BE SECURED WITH 4 LOCKNUTS.
SUPPLIED O RING TO BE POSITIONED BETWEEN KEYPAD AND FIXING PANEL PRIOR TO
INSTALLATION. OVERALL SIZES OF FIXING PANEL IS REPRESENTATIVE OF END USERS
PRODUCT ONLY.

PLEASE ENSURE THAT A SUITABLE PANEL MATERIAL IS USED TO SUPPORT THE KEYPAD.
THIS MUST PROVIDE SUFFICIENT RIGIDITY WHERE SEALING IS REQUIRED. E.G. 1.6mm
TO 2.0mm STEEL. THE UNDER SIDE OF THE PANEL SHOULD BE FLAT, CLEAN & FREE OF
DEBRIS TO OPTIMISE SEALING. THE TORQUE APPLIED TO THE LOCKNUT SHOULD NOT
EXCEED 50cNm.

Revision	Date	Revision	Date	Revision	Date
1	ECN101478	22.07.2015			



Storm Interface
14 Bentinck Court
Bentinck Road
West Drayton
Middlesex
UB7 7RQ, England

tel: +44 (0) 1895 431421
fax: +44 (0) 1895 431132
email: sales@storm-interface.com
website: www.storm-interface.com

Drawing Status	Title UNDER PANEL MOUNTING DETAILS FOR DIRECTIONAL KEYPAD				
Development	Material				
Drawn By & Date	Finish				
RC 22.7.2015	Scale 1:1				
Checked By & Date	Tool No.		Weight		
AC 19.08.2015	Unless Stated Tolerances		Angle Tol. ±0		
	0±		0.0± 0.2		0.00±
Approved By & Date	© Keymat Technology Ltd. The content of this communication and/or document, including but not limited to images, specifications, designs, concepts and information is confidential and is not to be used for any purpose or disclosed to a third party without the express and written consent of Keymat Technology Ltd., Copyright 2015. All rights reserved.			Part No.	Issue
JS 15.09.2015				132-00-33	1