



STORM AXS IS DESIGNED TO BE SECURED WITH 4 FIXINGS TO SUIT $\varnothing 4.5$ HOLE IN KEYPAD. TO MAINTAIN WATER TIGHT SEAL A GASKET (NOT SUPPLIED) TO BE POSITIONED BETWEEN KEYPAD AND FIXING PANEL PRIOR TO INSTALLATION. OVERALL SIZES OF FIXING PANEL IS REPRESENTATIVE OF END USERS PRODUCT ONLY.

PLEASE ENSURE THAT A SUITABLE PANEL MATERIAL IS USED TO SUPPORT THE KEYPAD. THIS MUST PROVIDE SUFFICIENT RIGIDITY WHERE SEALING IS REQUIRED. E.G. 1.6mm TO 2.0mm STEEL. THE UNDER SIDE OF THE PANEL SHOULD BE FLAT, CLEAN & FREE OF DEBRIS TO OPTIMISE SEALING.



Storm Interface
14 Bentinck Court
Bentinck Road
West Drayton
Middlesex
UB7 7RQ, England

tel: +44 (0) 1895 431421
fax: +44 (0) 1895 431132
email: sales@storm-interface.com
website: www.storm-interface.com

Drawing Status	Title UNDER PANEL MOUNTING DETAIL FOR DE1K		
Development	Material		
Drawn By & Date	Finish		
RC 2.10.2015			
Checked By & Date	Scale 1:1	Tool No.	Weight
AC 02.10.2015	Unless Stated Tolerances 0± 0.0± 0.2 0.00± 0.1	Angle Tol. ±0	
Approved By & Date	© Keymat Technology Ltd. The content of this communication and/or document, including but not limited to images, specifications, designs, concepts and information is confidential and is not to be used for any purpose or disclosed to a third party without the express and written consent of Keymat Technology Ltd., Copyright 2015. All rights reserved.		
JS 02.10.2015	Part No. DE1K-33		Issue 1