



THE UNDERPANEL NAV-BAR IS DESIGNED TO BE SECURED WITH 6 OFF M3 LOCKNUTS TO A PANEL WITH THREADED STUDS AS DETAILED ABOVE. ONCE SECURED, CABLE CAN BE FITTED TO CONNECTOR HEADER. OVERALL SIZES OF FIXING PANEL IS REPRESENTATIVE OF END USERS PRODUCT ONLY.

PLEASE ENSURE THAT A SUITABLE PANEL MATERIAL IS USED TO SUPPORT THE MODULE. THIS MUST PROVIDE SUFFICIENT RIGIDITY WHERE SEALING IS REQUIRED. E.G. 1.6mm TO 2mm STEEL. THE CLAMP SURFACE OF THE PANEL SHOULD BE FLAT, CLEAN & FREE OF DEBRIS TO OPTIMISE SEALING. TORQUE APPLIED TO LOCKNUT SHOULD NOT EXCEED 50cNm.



Storm Interface  
14 Bentinck Court  
Bentinck Road  
West Drayton  
Middlesex  
UB7 7RQ, England

tel: +44 (0) 1895 431421  
fax: +44 (0) 1895 431132  
email: sales@storm-interface.com  
website: www.storm-interface.com

Drawing Status	Title NAV-BAR UNDERPANEL INSTALLATION DRAWING				
Development	Material				
Drawn By & Date	Finish				
antho	Unless Stated Tolerances				
6.4.2017	0±	0.0±	0.2	0.00±	Angle Tol. ±0
Checked By & Date	Scale	Tool No.	Weight	Sheet	
RCH 7/4/17	1:1			1 of 1	
Approved By & Date	© Keymat Technology Ltd. The content of this communication and/or document, including but not limited to images, specifications, designs, concepts and information is confidential and is not to be used for any purpose or disclosed to a third party without the express and written consent of Keymat Technology Ltd., Copyright 2017. All rights reserved.			Part No.	Issue
JS 7/4/17				EB-06-331	1