



PLEASE ENSURE THAT A SUITABLE PANEL MATERIAL IS USED TO SUPPORT THE UNIT.
THIS MUST PROVIDE SUFFICIENT RIGIDITY WHERE SEALING IS REQUIRED.
THE UNDER SIDE OF THE PANEL SHOULD BE FLAT, CLEAN & FREE OF DEBRIS TO OPTIMISE SEALING.
THE TORQUE APPLIED TO THE LOCKNUT SHOULD NOT EXCEED 50cNm.

Revision	Date
Revision	Date
Revision 2	Date ECN101681 8.8.2019



*Storm Interface
1 Waterside Court,
Waterside Drive,
Langley,
Berkshire,
SL3 6EZ, England*

tel: +44 (0) 1895 431421
fax: +44 (0) 1895 431132
email: sales@storm-interface.com
website: www.storm-interface.com

Drawing Status Development	Title MOUNTING PANEL - MICROPHONE ARRAY				
Drawn By & Date RC 13.12.2018	Material 1.5mm STAINLESS STEEL				
Checked By & Date AC 8/8/19	Finish		Unless Stated Tolerances		
	0±	0.0±	0.00±	Angle Tol.	±0
	Scale 1:1	Tool No.	Weight	Sheet	1 of 1
Approved By & Date JS 8/8/19	© Keymat Technology Ltd. The content of this communication and/or document, including but not limited to images, specifications, designs, concepts and information is confidential and is not to be used for any purpose or disclosed to a third party without the express and written consent of Keymat Technology Ltd., Copyright 2018. All rights reserved.			Part No. 142-01-33	Issue 2