



DS66 KEYPAD MOUNTING PLATE IS DESIGNED TO BE SECURED WITH 2 SCREWS TO AN UPRIGHT / STANCHION / MULLION. ONCE SECURE AND CABLES FITTED TO CONNECTORS, FRONT ASSEMBLY CAN BE SNAPPED IN PLACE. OVERALL SIZES OF FIXING PANEL IS REPRESENTATIVE OF END USERS PRODUCT ONLY.

PLEASE ENSURE THAT A SUITABLE PANEL MATERIAL IS USED TO SUPPORT THE KEYPAD. THIS MUST PROVIDE SUFFICIENT RIGIDITY WHERE SEALING IS REQUIRED. THE CLAMP SURFACE OF THE PANEL SHOULD BE FLAT, CLEAN & FREE OF DEBRIS TO OPTIMISE SEALING.



Storm Interface
1 Waterside Court
Waterside Drive
Langley
Berkshire
SL3 6EZ, England

tel: +44 (0) 1895 431421
email:sales@storm-interface.com
website:www.storm-interface.com

Drawing Status	Title				
Production	MOUNTING DETAILS FOR DS66				
Drawn By & Date	Material				
Chris 28.10.2020	Finish				
Checked By & Date	Scale	1:1	Tool No.	Weight	
AC 28.10.2020	Unless Stated Tolerances		0±	0.0± 0.2	0.00±
Approved By & Date	© Keymat Technology Ltd. The content of this communication and/or document, including but not limited to images, specifications, designs, concepts and information is confidential and is not to be used for any purpose or disclosed to a third party without the express and written consent of Keymat Technology Ltd., Copyright 2020. All rights reserved.			Part No.	Issue
JS 28.10.2020				156-00-33	1
	Angle Tol.				±0